



## High Brightness Panel

### SPECIFICATIONS

|                          |   |
|--------------------------|---|
| <b>Model No.</b>         | <b>HB280LAUW-L15 V.0</b>                  |
| Screen Diagonal          | 28 inch                                   |
| Active Area              | 698.4 mm(H) × 129.86 mm(V)                |
| Resolution               | 1920 × 3(RGB) × 358                       |
| Pixel Pitch              | 0.3637 mm × 0.3637 mm (per one triad)     |
| Color                    | 16.7M                                     |
| White Luminance (Center) | 1500 cd/m <sup>2</sup> (max)              |
| View Angle (R/L/U/D)     | 89° / 89° / 89° / 89° (CR ≥ 10)           |
| Contrast Ratio           | 3000 : 1                                  |
| Interface                | 2 channel LVDS                            |
| Surface Treatment        | Anti-glare type, Hardness 3H              |
| Operation Temperature    | -0 °C ~ 50 °C                             |
| Storage Temperature      | -20 °C ~ 60 °C                            |
| Outline Dimension        | 733.78 mm(H) × 165.34 mm (V) × 17.9 mm(D) |
| Weight                   | 1100 g                                    |

Elshine Technology (GoodSoil Electric) Co.,Ltd.

TEL: + 886-2-22889604

Mail:caleb@elshine.com.tw

<http://www.elshine.com.tw>